

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 20.07.2016 Revision date: 29.11.2023 Supersedes version of: 04.03.2021 Version: 4.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product form : Mixture  
Trade name : UR 01 PU PRIMER LIGHT GREY  
UFI : HP76-DPNT-2M34-90RY  
Product code : 39-100667

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.2.1. Relevant identified uses

Main use category : Industrial use

## 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

## Manufacturer

Orgachim JSC  
21 Treti Mart Blvd  
7000 Ruse – Bulgaria  
Bulgaria  
T +359 82 886 222 - F +359 82 886 221  
[orgachim@orgachim.bg](mailto:orgachim@orgachim.bg) - [www.orgachim.bg](http://www.orgachim.bg)

## Supplier

S.C. POLICOLOR S.A.  
Bdul Timisoara nr.98, sector.6  
061334 Bucharest – Romania  
Romania  
T +40 213 451 730 - F +40 213 451 930  
[msds@policolor.ro](mailto:msds@policolor.ro) - [www.policolor.ro](http://www.policolor.ro)

## 1.4. Emergency telephone number

Emergency number : Unified emergency number: 112;

Country	Organisation/Company	Address	Emergency number	Comment
Australia	NSW Poisons Information Centre The Children's Hospital at Westmead	Locked Bag 4001 NSW 2145	13 11 26	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
STOT RE 2 H373

Full text of hazard classes, H- and EUH-statements: see section 16

## Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: xylene

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H373 - May cause damage to organs (lungs, skin) through prolonged or repeated exposure (if inhaled, if swallowed, Inhalation, in contact with skin).

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P314 - Get medical advice/attention if you feel unwell.  
P337+P313 - If eye irritation persists: Get medical advice/attention.

EUH-statements

: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.  
EUH208 - Contains Fatty acids, tall-oil, compds. with oleylamine(85711-55-3). May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

Extra phrases

: For professional users only.

### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
Titanium Dioxide (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
chalk (1317-65-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Fatty acids, tall-oil, compds. with oleylamine(85711-55-3)	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
chalk substance with national workplace exposure limit(s) (BE, BG, FR, GB)	CAS-No.: 1317-65-3 EC-No.: 215-279-6	34 – 50	Not classified
xylene substance with national workplace exposure limit(s) (BG, DE, FR, GB, RO); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	14,5 – 25,5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Titanium Dioxide substance with national workplace exposure limit(s) (BE, BG, FR, GB, RO)	CAS-No.: 13463-67-7 EC-No.: 236-675-5	5 – 10	Carc. 2, H351
n-butyl acetate substance with national workplace exposure limit(s) (BG, DE, FR, GB, RO); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	3 – 5,25	Flam. Liq. 3, H226 STOT SE 3, H336
Fatty acids, tall-oil, compds. with oleylamine	CAS-No.: 85711-55-3 EC-No.: 288-315-1	0,02 – 0,125	Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT RE 2, H373

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-butyl acetate (123-86-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup> 723 mg/m <sup>3</sup>
IOEL STEL [ppm]	150 ppm 150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831 COMMISSION DIRECTIVE (EU) 2019/1831
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	n-Бутилацетат
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL	150 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
<b>France - Occupational Exposure Limits</b>	
Local name	Acétate de n-butyle
VME (OEL TWA)	710 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	150 ppm
VLE (OEL C/STEL)	940 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	200 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	300 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	62 ppm
Peak exposure limitation factor	2(l)
Remark	AGS - Ausschuss für Gefahrstoffe; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Romania - Occupational Exposure Limits</b>	
Local name	Acetat de n-butil
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA	50 ppm
OEL STEL	723 mg/m <sup>3</sup>

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-butyl acetate (123-86-4)</b>	
OEL STEL	150 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>xylene (1330-20-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Ксилен (смес от изомери), чист
OEL TWA	221 mg/m <sup>3</sup>
OEL TWA	50 ppm
OEL STEL	442 mg/m <sup>3</sup>
OEL STEL	100 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
<b>France - Occupational Exposure Limits</b>	
Local name	Xylène, isomères mixtes, purs
VME (OEL TWA)	221 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	50 ppm
VLE (OEL C/STEL)	442 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	100 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>xylene (1330-20-7)</b>	
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	220 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	50 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv
Regulatory reference	TRGS900
<b>Germany - Biological limit values (TRGS 903)</b>	
Local name	Xylol (alle Isomere)
Biological limit value	2000 mg/l Parameter: Methylhippur-(Tolur-) säure (alle Isomere) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
<b>Romania - Occupational Exposure Limits</b>	
Local name	Xilen, izomer mixt, pur
OEL TWA	221 mg/m <sup>3</sup>
OEL TWA	50 ppm
OEL STEL	442 mg/m <sup>3</sup>
OEL STEL	100 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>Romania - Biological limit values</b>	
Local name	Xilen
BLV	3 g/l Indicator biologic: Acid metilhipuric - Material biologic: urină - Momentul recoltării: sfârșit schimb
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Titanium Dioxide (13463-67-7)	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup>
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Титанов диоксид
OEL TWA	10 mg/m <sup>3</sup> (респирабилен прах)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
<b>France - Occupational Exposure Limits</b>	
Local name	Titane (dioxyde de), en Ti
VME (OEL TWA)	10 mg/m <sup>3</sup>
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Romania - Occupational Exposure Limits</b>	
Local name	Dioxid de titan
OEL TWA	10 mg/m <sup>3</sup>
OEL STEL	15 mg/m <sup>3</sup>
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m <sup>3</sup> respirable 10 mg/m <sup>3</sup> total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	10 mg/m <sup>3</sup>
<b>chalk (1317-65-3)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup>
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Калциев карбонат
OEL TWA	10 mg/m <sup>3</sup> 10 mg/m <sup>3</sup> Инхалабилна фракция
OEL TWA	1 ppm Влакна - респирабилна фракция
<b>France - Occupational Exposure Limits</b>	
VME (OEL TWA)	10 mg/m <sup>3</sup>
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> total inhalable 4 mg/m <sup>3</sup> respirable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE



# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Light grey.
Odour	: aromatic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 124 °C
Flammability	: Not available
Lower explosion limit	: 1,1 vol %
Upper explosion limit	: 7 vol %
Flash point	: 30 °C

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature	: 500 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Water:
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1,5 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### xylene (1330-20-7)

LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
--------------------	---

#### Titanium Dioxide (13463-67-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
---------------	--

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Titanium Dioxide (13463-67-7)</b>	
LC50 Inhalation - Rat	> 5,09 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
<b>chalk (1317-65-3)</b>	
LD50 oral rat	6450 mg/kg (Rat, Literature study, Oral)
Skin corrosion/irritation	: Causes skin irritation.
<b>n-butyl acetate (123-86-4)</b>	
pH	6,2 Temp.: 20 °C Concentration: (≈)5 g/L
<b>Titanium Dioxide (13463-67-7)</b>	
pH	7
<b>chalk (1317-65-3)</b>	
pH	8,5 – 9
Serious eye damage/irritation	: Causes serious eye irritation.
<b>n-butyl acetate (123-86-4)</b>	
pH	6,2 Temp.: 20 °C Concentration: (≈)5 g/L
<b>Titanium Dioxide (13463-67-7)</b>	
pH	7
<b>chalk (1317-65-3)</b>	
pH	8,5 – 9
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>xylene (1330-20-7)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (lungs, skin) through prolonged or repeated exposure (if inhaled, if swallowed, Inhalation, in contact with skin).
<b>xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Fatty acids, tall-oil,compds. with oleylamine (85711-55-3)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
<b>n-butyl acetate (123-86-4)</b>	
Viscosity, kinematic	0,83 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
<b>Titanium Dioxide (13463-67-7)</b>	
Viscosity, kinematic	Not applicable (solid)

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### chalk (1317-65-3)

Viscosity, kinematic	No data available in the literature
----------------------	-------------------------------------

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

### n-butyl acetate (123-86-4)

LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	674,7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### xylene (1330-20-7)

LC50 - Fish [1]	2,6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

### Titanium Dioxide (13463-67-7)

LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19,3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27,8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 2,92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### chalk (1317-65-3)

LC50 - Fish [1]	> 10000 mg/l (96 h, Oncorhynchus mykiss, Literature study)
EC50 - Crustacea [1]	> 1000 mg/l (48 h, Daphnia magna, Literature study)
EC50 72h - Algae [1]	> 200 mg/l (Desmodesmus subspicatus, Literature study)

### 12.2. Persistence and degradability

### Titanium Dioxide (13463-67-7)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Titanium Dioxide (13463-67-7)	
ThOD	Not applicable (inorganic)
chalk (1317-65-3)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

### 12.3. Bioaccumulative potential

Titanium Dioxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.
chalk (1317-65-3)	
Bioaccumulative potential	Bioaccumulation: not applicable.

### 12.4. Mobility in soil

Titanium Dioxide (13463-67-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
chalk (1317-65-3)	
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Results of PBT and vPvB assessment

UR 01 PU PRIMER LIGHT GREY	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Component	
Titanium Dioxide (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
chalk (1317-65-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW, EC 2000/532)	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances






# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878


### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>				
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
<b>Transport document description</b>				
UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E)	UN 1263 PAINT RELATED MATERIAL, 3, III (30°C c.c.)	UN 1263 Paint related material, 3, III	UN 1263 PAINT RELATED MATERIAL, 3, III	UN 1263 PAINT RELATED MATERIAL, 3, III
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Transport category (RID)	: 3
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 33

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

## 15.1.2. National regulations

### France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamide; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

### Germany

Water hazard class (WGK)

: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510)

: LGK 3 - Flammable liquids.

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 2A, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.1B, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for

: LGK 5.1B, LGK 6.1D, LGK 11, LGK 10-13.

Joint storage permitted for

: LGK 2B, LGK 3, LGK 6.1A, LGK 6.1C, LGK 8A, LGK 8B, LGK 10, LGK 12, LGK 13.

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

SZW-lijst van kankerverwekkende stoffen

: None of the components are listed

SZW-lijst van mutagene stoffen

: None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: None of the components are listed

SZW-lijst van reprotoxische stoffen –

: None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

: xylene is listed

### Denmark

Class for fire hazard

: Class II-1

Store unit

: 5 liter

Classification remarks

: R10 <H226;H315;H319;H373>; Emergency management guidelines for the storage of flammable liquids must be followed



# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### Switzerland

Storage class (LK) : LK 3 - Flammable liquids

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

**For the following substances of this mixture a chemical safety assessment has been carried out:**

n-butyl acetate

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant

# UR 01 PU PRIMER LIGHT GREY

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH208	Contains Fatty acids, tall-oil, compds. with oleylamine(85711-55-3). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.